Submit To: Office of the City Engineer

City of West Lafayette Application for Stormwater Permit



	e of the City Engineer Application for Stormwater Permit N Chauncey Ave (to be completed by Applicant)	WEST ************************************		
	t Lafayette, IN 47906 engineering@wl.in.gov (765) 807-8980	Engineering		
Project Name:				
	ral Location:			
File Number: Date Completed:				
1. Application Fee				
1. Application ree				
Check Attached				
2. Notice of Intent				
	Completed Notice of Intent State Form #47487			
3. Construction Plans				
	Project narrative and supporting documents, including the following information:			
	An index indicating the location, in the construction plans, of all information require subsection.	d by this		
	Description of the nature and purpose of the project.			
	Legal description of the project site. The description should be to the nearest quart	er		
	section, township, and range, and include the civil township. Soil properties, characteristics, limitations, and hazards associated with the project	t cita and		
	the measures that will be integrated into the project to overcome or minimize adve			
	conditions.			
	General construction sequence of how the project site will be built, including phase	s of		
	construction.			
	14-Digit Watershed Hydrologic Unit Code.	ad laves it		
	A reduced plat or project site map showing the lot numbers, lot boundaries, and ro and names. The reduced map must be legible and submitted on a sheet or sheets			
	than eleven (11) inches by seventeen (17) inches for all phases or sections of the			
	site.	'		
	A general site plan exhibit with the proposed construction area superimposed on a			
	GIS ortho-aerial map at a scale of 1"=100'. The exhibit should provide 2-foot conto			
	information and include all roads and buildings within a minimum 500' radius beyon project boundaries.	na tne		
	Identification of any other state or federal water quality permits that are required fo	r		
	construction activities associated with the owner's project site.			
	Vicinity map depicting the project site location in relationship to recognizable local landma			
	towns, and major roads, such as a USGS topographic quadrangle map, or county or mun	icipal		
	road map. An existing project site layout that must include the following information:			
	Location, name, and normal water level of all wetlands, lakes, ponds, and water co	ourses on		
	or adjacent to, the project site.	, 4, 555 511,		
	Location of all existing structures on the project site.			
	One hundred (100) year floodplains, floodway fringes, and floodways. Please note	if none		
	exists.			
	Soil map of the predominant soil types, as determined by the United States Depart			
	Agriculture (USDA), Natural Resources Conservation Service (NRCS) Soil Survey, determined by a soil scientist. Hydrologic classification for soils should be shown in			
	hydrologic methods requiring soils information are used. A soil legend must be inc			
	with the soil map.			
	Identification and delineation of vegetative cover such as grass, weeds, brush, and	trees on		
	the project site.			
	Location of storm, sanitary, combined sewer, and septic tank systems and outfalls.			

	Land use of all adjacent properties.
	Identification and delineation of sensitive areas.
	Existing topography at a contour interval appropriate to indicate drainage patterns.
	The location of regulated drains, farm drains, inlets and outfalls, if any of record.
	Final project site layout, including the following information:
	Location of all proposed site improvements, including roads, utilities, lot delineation and
	identification, proposed structures, and common areas.
	One hundred (100) year floodplains, floodway fringes, and floodways. Please note if none
	exists.
	Proposed final topography, at a contour interval appropriate to indicate drainage patterns.
	A grading plan, including the following information:
	Delineation of all proposed land disturbing activities, including off-site activities that will
	provide services to the project site.
	Location of all soil stockpiles and borrow areas.
	Information regarding any off-site borrow, stockpile, or disposal areas that are associated
	with a project site, and under the control of the project site owner.
	Existing and proposed topographic information.
	A drainage plan, including the following information:
	An estimate of the peak discharge, based on the ten (10) year storm event, of the project
	site for both pre-construction and post-construction conditions.
	Calculation showing peak runoff rate after development for the 10-year and 100-year return
	period storms of critical duration do not exceed the 2-year and 10-year return period pre-
	development peak runoff rates, respectively.
	Location, size, and dimensions of all existing streams to be maintained, and new drainage
	systems such as culverts, bridges, storm sewers, and conveyance channels.
	Locations where stormwater may be directly discharged into groundwater, such as
	abandoned wells or sinkholes. Please note if none exists.
	Locations of specific points where stormwater discharge will leave the project site.
	Name of all receiving waters. If the discharge is to a separate municipal storm sewer,
	identify the name of the municipal operator and the ultimate receiving water.
	Location, size, and dimensions of features such as permanent retention or detention
	facilities, including existing or manmade wetlands, used for the purpose of stormwater
	management. Include existing retention or detention facilities that will be maintained,
	enlarged, or otherwise altered and new ponds or basins to be built and the basis of their
	design.
	The estimated depth and amount of storage required by design of the new ponds or basins.
	One or more typical cross sections of all existing and proposed channels or other open
	drainage facilities carried to a point above the 100-year high water and showing the
	elevation of the existing land and the proposed changes, together with the high water
	elevations expected from the 100 year storm under the controlled conditions called for by
	this ordinance, and the relationship of structures, streets, and other facilities
4. St	tormwater Drainage Technical Report
	A summary report, including the following information:
	A summary report, including the following information: The significant drainage problems associated with the project;
	The significant dramage problems associated with the project, The analysis procedure used to evaluate these problems and to propose solutions;
	Any assumptions or special conditions associated with the use of these procedures,
	especially the hydrologic or hydraulic methods;
	The proposed design of the drainage control system; and
	The proposed design of the drainage control system, and The results of the analysis of the proposed drainage control system showing that it does
	solve the project's drainage problems. Any hydrologic or hydraulic calculations or modeling
	results must be adequately cited and described in the summary description. If hydrologic or
	hydraulic models are used, the input and output files for all necessary runs must be included in the appendices. A man showing any drainage area subdivisions used in the analysis
	in the appendices. A map showing any drainage area subdivisions used in the analysis
	must accompany the report.

	A Hydrologic/Hydraulic Analysis, consistent with the methodologies and calculation included in the		
	[technical standards], and including the following information:		
	A hydraulic report detailing existing and proposed drainage patterns on the subject site. The		
	report should include a description of present land use and proposed land use. Any off-site		
	drainage entering the site should be addressed as well. This report should be		
	comprehensive and detail all of the steps the engineer took during the design process.		
	All hydrologic and hydraulic computations should be included in the submittal. These		
	calculations should include, but are not limited to: runoff curve numbers and runoff		
	coefficients, runoff calculations, stage-discharge relationships, times-of-concentration and		
	storage volumes.		
	Copies of all computer runs. These computer runs should include both the input and the		
	outputs. Electronic copies of the computer runs with input files will expedite the review		
	process.		
	A set of exhibits should be included showing the drainage sub-areas and a schematic		
	detailing of how the computer models were set up. A conclusion which summarizes the hydraulic design and details how this design satisfies		
	this ordinance.		
	tilis ordinance.		
5. St	ormwater Pollution Prevention Plan for Construction Sites		
	Location, dimensions, detailed specifications, and construction details of all temporary and		
	permanent stormwater quality measures.		
	Temporary stabilization plans and sequence of implementation.		
	Permanent stabilization plans and sequence of implementation.		
	Temporary and permanent stabilization plans shall include the following:		
	Specifications and application rates for soil amendments and seed mixtures.		
	The type and application rate for anchored mulch.		
	Construction sequence describing the relationship between implementation of stormwater quality		
	measures and stages of construction activities.		
	A typical erosion and sediment control plan for individual lot development.		
	Self-monitoring program including plan and procedures.		
	A description of potential pollutant sources associated with the construction activities, which may		
	reasonably be expected to add a significant amount of pollutants to stormwater discharges. Material handling and storage associated with construction activity shall meet the spill prevention		
	and spill response requirements in 327 IAC 2-6.1.		
	and spill response requirements in 327 I/O 2 0.1.		
6. Po	st-Construction Storm Water Pollution Prevention Plan		
	A description of potential pollutant sources from the proposed land use, which may reasonably be		
	expected to add a significant amount of pollutants to stormwater discharges.		
	Location, dimensions, detailed specifications, and construction details of all post-construction		
	stormwater quality measures.		
	A description of measures that will be installed to control pollutants in stormwater discharges that		
	will occur after construction activities have been completed. Such practices include infiltration of		
	run-off, flow reduction by use of open vegetated swales and natural depressions, buffer strip and		
	riparian zone preservation, filter strip creation, minimization of land disturbance and surface		
	imperviousness, maximization of open space, and stormwater retention and detention ponds.		
	A sequence describing when each post-construction stormwater quality measure will be installed.		
	Stormwater quality measures that will remove or minimize pollutants from stormwater run-off.		
	Stormwater quality measures that will be implemented to prevent or minimize adverse impacts to		
	stream and riparian habitat.		
	A narrative description of the maintenance guidelines for all post-construction stormwater quality		
	measures to facilitate their proper long term function. This narrative description shall be made		
	available to future parties who will assume responsibility for the operation and maintenance of the		
	post-construction stormwater quality measures.		